

DECK OR TUB WALL-MOUNT FAUCET

INSTALLATION INSTRUCTIONS

BEFORE YOU BEGIN

Before installing, read entire Installation Instructions. Observe all local building and safety codes.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-866-855-2284. If you need assistance or have questions while installing your faucet, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures and plumbing. Signature Hardware accepts no liability for any damages to the floor, walls, plumbing or for personal injury during installation.

Shut off the water supply lines at the tub where the new faucet is being installed.

GETTING STARTED

- Ensure that you have gathered all the required materials that are needed for the installation.
- For these instructions, it is assumed that the old faucet has been completely removed and any necessary repairs or modifications to the water supply have been completed.

TOOLS AND MATERIALS:



Adjustable
Wrench



Basin
Wrench

INSTALLATION

1. Remove lock nuts from the back or bottom of the faucet and insert faucet through mounting holes.
2. Hand-tighten washers (if included) and hex nuts to secure.
3. Check to make sure the faucet is properly aligned and adjust as needed. When the faucet is in the proper position, finish tightening the hex nuts with your adjustable wrench.
4. Attach the hot and cold water feed tubes to the water inlets on the back, or bottom of the faucet. (Hot water is always on the left and cold water is always on the right)
5. Finish your installation by attaching any hoses and/or handles that might be included.
6. After all connections have been made, turn on the water supply, check to make sure that all connections are tight (no water should be leaking) and that the hot and cold supplies are working correctly. Turn the faucet on and allow the water to flow through the spout for approximately 60 seconds. If you have a hand shower, divert the water to the hose and allow the water to flow through the hose for an additional 60 seconds.

REVISED 03/15/2019